Webbing slings



Features

- According to EN 1492-1.
- Safety factor 7:1.
- Made of polyester (PES).
- With capacity stripes.
- Stitched label with additional protective cover.
- With double webbing and reinforced eyes.
- Available in different lengths according to EN standard colour coded.
- Complies with the Machinery Directive 2006/42/EC. Supplied with test certificate, CE declaration of conformity and operating instructions.

Specifications							
Article code	Capacity					Webbing width	Colour
	single	choker	double	double	double		
	ton	ton	ton	ton	ton	mm	
				 7-45°	 45-60°		
CO.HL.01	1,000	0,800	2,000	1,400	1,000	30	
CO.HL.02	2,000	1,600	4,000	2,800	2,000	60	
CO.HL.03	3,000	2,400	6,000	4,200	3,000	90	
CO.HL.04	4,000	3,200	8,000	5,600	4,000	120	
CO.HL.05	5,000	4,000	10,000	7,000	5,000	150	
CO.HL.06	6,000	4,800	12,000	8,400	6,000	180	
CO.HL.08	8,000	6,400	16,000	11,200	8,000	210	
CO.HL.10	10,000	8,000	20,000	14,000	10,000	240	
CO.HL.12	12,000	9,600	24,000	16,800	12,000	300	

Subject to changes without notice. Illustrations for reference only. Always obey the operating instructions.
2025 © DELTA® Hoisting Equipment E1411250952