Roundslings



Features

- According to EN 1492-2.
- Safety factor 7:1.
- Made of polyester (PES).
- With capacity stripes.
- Stitched label with additional protective cover.
- Available in different lengths according to EN standard colour coded.
- Complies with the Machinery Directive 2006/42/EC. Supplied with test certificate, CE declaration of conformity and operating instructions.

Specifications							
Article code	Capacity					Webbing width	Colour
	single	choker	double	double	double		
	ton	ton	ton	ton	ton	mm	
				 7-45°	 45-60°		
CO.RS.01	1,000	0,800	2,000	1,400	1,000	45	
CO.RS.02	2,000	1,600	4,000	2,800	2,000	55	
CO.RS.03	3,000	2,400	6,000	4,200	3,000	60	
CO.RS.04	4,000	3,200	8,000	5,600	4,000	65	
CO.RS.05	5,000	4,000	10,000	7,000	5,000	70	
CO.RS.06	6,000	4,800	12,000	8,400	6,000	75	
CO.RS.08	8,000	6,400	16,000	11,200	8,000	85	
CO.RS.10	10,000	8,000	20,000	14,000	10,000	110	
CO.RS.12	12,000	9,600	24,000	16,800	12,000	160	

Subject to changes without notice. Illustrations for reference only. Always obey the operating instructions.
2025 © DELTA® Hoisting Equipment E1411250953