



**“All New  
COMPACT!”**



This device complies with Part  
Operation is subject to the follo  
(1) this device may not cause har  
(2) this device must accept any  
including interference that may ca

**Frequency band**

315 / 418 / 429 / 433 / 447 /  
470 / 868 / 915 MHz / 2.4 GHz

**Number of functions**

up to 3 on/off + EMO

**Power supply**

90~460V AC / DC

**Stop/Safety contact rating**

6A

**Command contact rating**

5A (250V AC)

**Command response time**

~ 25 ms

**Safety category for the  
Stop protection (EN ISO 13849-1)**  
PL d (optional)

**Operating and storage temperature**

(-20°C)~(+55°C) / (-40°C)~(+65°C)

**Protection degree**

IP65

**Housing material**

PA6 (GF30%)

- Status LED
- Internal BootLoader,  
up firmware to the date  
by using computer
- Wireless pairing to transmitter

**Weight**

approx. 295g

**Size**

122×86×34mm

**Antenna**

Internal  
SMA External  
SMA 2M / 5M cable magnetic







**So Mini, so Lightweight**  
 Due to its small size, you can install it easily and need not too much space.

**Pretend to be Wireless**  
 It can be connected with the wire through the hole at the back of the device.



“X200B practical usage”

**Considerate Buttons**

You can operate the receiver directly without the transmitter — just push the buttons on the receiver. Moreover, it can be operated simultaneously by two people.



