



Overhead crane end carriages  
Underslung end carriages  
Geared motors

UNDERSLUNG END CARRIAGES  
Low headroom type

Technical data

Type	Max Capacity	Max span	Wheelbase	Speed	Motor power single speed suitable for inverter	Motor power double speed	Crane beam Min/Max	Wheels diameter øW	L1	hm	h1	h2	Max beam thickness	Lf	
	T	m	mm	m/min			mm	mm	mm	mm	mm	mm	mm	mm	
M20/6	2T	6	1000	20	20/5	2x0,18	2x0,18/0,06	110/300	80	195	100	140	65	20	25
M20/10		10	1500	20	20/5	2x0,18	2x0,18/0,06	110/130		195	100	140	65	20	25
M20/14		14	2000	20	20/5	2x0,18	2x0,18/0,06	110/130		195	100	140	65	20	25
M30/6	3T	6	900	20	20/5	2x0,18	2x0,18/0,06	110/300	80	195	100	140	65	20	25
M30/10		10	1500	20	20/5	2x0,18	2x0,18/0,06	110/130		195	100	140	65	20	25
M30/14		14	2000	20	20/5	2x0,18	2x0,18/0,06	110/130		195	100	140	65	20	25
M50/6	5T	6	1000	18	18/6	2x0,37	2x0,37/0,10	120/300	120	260	160	210	65	25	35
M50/10		10	1500	18	18/6	2x0,37	2x0,37/0,10	120/300		260	160	210	65	25	35
M50/14		14	2000	18	18/6	2x0,37	2x0,37/0,10	120/300		260	160	210	65	25	35
M50/20		20	3000	18	18/6	2x0,37	2x0,37/0,10	120/300		260	160	210	65	25	35
M63/6	6,3	6	1000	18	18/6	2x0,37	2x0,37/0,10	120/300	120	260	160	210	65	25	35
M63/10		10	1500	18	18/6	2x0,37	2x0,37/0,10	120/300		260	160	210	65	25	35
M63/14		14	2000	18	18/6	2x0,37	2x0,37/0,10	120/300		260	160	210	65	25	35
M63/20		20	3000	18	18/6	2x0,37	2x0,37/0,10	120/300		260	160	210	65	25	35
M100/6	10	6	1000	18	18/6	2x0,55	2x0,55/0,18	120/300	140	290	170	230	70	25	40
M100/10		10	1500	18	18/6	2x0,55	2x0,55/0,18	120/300		290	170	230	70	25	40
M100/14		14	2000	18	18/6	2x0,55	2x0,55/0,18	120/300		290	170	230	70	25	40
M100/20		20	3000	18	18/6	2x0,55	2x0,55/0,18	120/300		290	170	230	70	25	40

